

Norphonic VoIP panel phone assembly - Berg Handset

- Excellent sound quality (STI = 0.9)
- Robust

Assembling the Berg handset with a Holme base results in a panel phone which can be used in a wide array of applications. The only requirements are for the panel to be cut-out contour to be as the one shown in the picture below. Please refer to our manual for more assembly details.

The handset consists of ahigh quality microphone and speaker, designed and tested for rugged environments. The robust handset and armoured cord ensure excellent protection against harsh environments.



Technical Specifications

Weather resistance: Dust and waterproof to

IP65 (Dependent on mounting)

Heavy duty performance: Impact-, fall-,

vibration- and shock--proof, able to perform in

difficult environments

Operating temperatures: -25° C to + 65° C Relative humidity high: 93% R.H at 40° C (non-

condensing)

Casing material: Polycarbonate

Weight: 0.54kg (with Holme 1.20kg)s **Handset:** Robust handset with armoured stainless steel cord IP65Hook-switch:

Magnetic with no mechanical moving parts **Microphone:** Noise cancelling dynamic mic,

proven in noisy areas. **Speaker:** 500hm 1W

Excellent sound quality: STI approved to 0.9

(Excellent Sound)

Colour: Black handset with yellow front panel. **Weight:** 1.20 kg approx. (0.65kg Holme only) **Power supply:** 24V-48V DC input, or Power

over Ethernet (PoE)

Power consumption: 3W nominal, 5W start-


au


Connection: RJ11 plug for Handset

Microphone and Speaker, 2-pin terminal plug

for hook. Earthing cable.

Dimensions





Approvals

EN 50121-4:2016A 1:2019 - Railway Applications

EN 55032:2015 AC:2016, EN 55035:2017 AC:2019 - Electromagnetic compatibility of multimedia equipment

Order Codes

Berg handset assembly 1110010
With 0,8m handset cable
Berg handset assembly 1110012
with 1m handset cable

Learn more about our Innovations at www.norphonic.com

Fjellsdalen 3, 5155 Bønes, Norway +47 55 62 75 20 sales@norphonic.com

